

WINDOW INTERCOM

SD-2006V+



Features

**Duplex Intercom**

SD-2006V+ supports two-way intercom inside and outside the window.

**Clear sound | Volume adjustment**

The voice is clear, natural and loud. That support the sound inside and outside the window, and the volume can be adjusted

**Recording output**

It supports headphone jack, and can output two-way sound signals inside and outside the window

**Easy to Use**

Plug and Play, Easy installation, support desktop placement or wall mounted.
Power adapter(DC12V/200mA)



- Stainless steel hose microphone tube can be folded without any dead angle.
- Equipped with window microphone, 3M adhesive tape is directly pasted on the window glass, easy to install.

Technical Specifications

Host speaker impedance power:	8 Ω , 2W
Extension speaker impedance power:	8 Ω , 2W
Host microphone sensitivity:	- 51 \pm 2dB
Output frequency	20Hz~20KHz
Sensitivity of extension microphone:	- 44 \pm 2dB
Signal to noise ratio:	\geq 90dB
Harmonic distortion:	< 0.5%
Working temperature:	- 20 $^{\circ}$ C ~ + 60 $^{\circ}$ C
Working humidity:	10% - 90%
Host size:	80x150x55mm
Extension size:	55x100x80mm
Microphone length:	360mm

Interface Connection

1 Counter Intercom Control (Host)

- Volume control button
- Counter MIC switch
- Indicator light

2 External Speaker Control (Sub)

- Volume control button
- Counter MIC switch
- Indicator light

3 OUT

Connection jack of External Speaker (Sub).

4 MIC.

Internal MIC 3.5mm jack.

5 REC.

Record, monitor and interjection 3.5mm jack.

6 POWER


Power jack for power supply DC12V / 0.2A.




Package Includes



1 x Dual-way counter intercom



1 x External speaker



1 x Power adapter with cable



1 x English manual